

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
7 April 2005 (07.04.2005)

PCT

(10) International Publication Number
WO 2005/031231 A1

- (51) International Patent Classification⁷: **F26B 21/08**
- (21) International Application Number:
PCT/JP2004/014417
- (22) International Filing Date:
24 September 2004 (24.09.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2003-333221 25 September 2003 (25.09.2003) JP
- (71) Applicant (for all designated States except US): MAT-SUSHITA ELECTRIC INDSTRIAL CO. LTD. [JP/JP]; 1006, Oazakadoma Kadoma-shi, Osaka 571-8501 (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): TAMURA, Tomoichiro [JP/JP]; ** (JP). YAKUMARU, Yuuichi [JP/JP]; ** (JP). NISHIWAKI, Fumitoshi [JP/JP]; ** (JP).
- (74) Agents: SHIMIZU, Yoshihiro et al.; 3rd Floor, Yashiro Building, 14-4, Takadanobaba 2-chome, Shinjuku-ku, Tokyo 169-0075 (JP).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HEAT PUMP TYPE DRYING APPARATUS DRYING APPARATUS AND DRYING METHOD



(57) Abstract: A drying apparatus has a heat pump comprising a compressor (31), a radiator (32), a throttle apparatus (33) and an evaporator (34), and also includes a structure in which drying air heated by heat of the radiator (32) is introduced to a subject (37) to be dried is dehumidified by the evaporator (34). The drying apparatus also includes a bypass circuit (39) through which a portion of drying air heated by the radiator (32) flows to an inlet of the evaporator (34) without coming into contact with the subject, a super heat detecting device (43, 44) for detecting super heat of the heat pump apparatus, and a throttle apparatus control device for controlling flow path resistance in the bypass circuit (39) using a value detected by the super heat detecting device (43, 44).